




COLOR:  
**EMPIRE**

SKU #:  
**58769T**



**Height: 5/8" Length: 82-5/8" RL**

*All dimensions are nominal*



*Your floor may vary due to color treatment, natural tannin variations and knots.*

**Wood Species:**  
French White Oak

**Grade:**  
Prime

**Construction:**  
3-ply engineered, cold pressed

**Wear Layer:**  
4mm sawn cut, dry sawn, resandable up to 3 times

**Glue:**  
Free of Formaldehyde, Carb II compliant

**Style:**  
Wire brushed, bevel 4-sides, T&G  
Fumed and lime-washed colors

**Finish:**  
UV-cured Urethane, brush matte, 6-8% gloss  
Static Friction Coefficient (ASTM D 2047): slip resistance < 0.5

**Warranty:**  
50 Years Surface, Lifetime Structural

**Coverage:**  
25.85 sq ft / carton

**Installation:**  
Glue, float or nail with glue assist

**Subfloor:**  
Wood, concrete or radiant floor systems

**Radiant Heat:**  
Yes, glue down or floating installation > 83° F

ENVIRONMENT: **No harmful VOC, GREENGUARD Gold certified, LEED credits**

**CERTIFIED MANUFACTURING:**

- GREENGUARD Gold certified
- Lacey Act and Prop 65 compliant
- No added Urea Formaldehyde, NAF
- No halogenated hydrocarbons, herbicides, heavy metals
- 100% PEFC (PanEuro Forest Council) material  
*100% chain of custody from forest to jobsite*

**GREEN BUILD STATEMENT:**

*Palladio Hardwood Flooring may contribute to attaining points within the Environmental Quality section of the LEED rating system. The determining factor for indoor quality is the quantity of noxious emanations from volatile compounds in adhesives and finishes.*



**TEST RESULTS:**

**Emissions Test:**  
CA - DPH specification 01350 (Prop 65): Pass

**Delamination Test:**  
ANSI/HPVA Bond Line 3 Cycle Test: 100% Pass

**Critical Radial Flux:**  
avg 0.37 w/cm2 ASTM E 648, Class 2 NFPA Life Safety Code 101

**NWFA Janka (Hardness):**  
1360 lbs

**Surface Burning:**  
ASTM E84 Class C

**Smoke Density:**  
Avg.DMC 281-389 Non Flaming ASTM E 662