


COLOR: SADDLE

28005



All dimensions are nominal



Your floor may vary due to color treatment, natural tannin variations and knots.

Wood Species:

White Oak

Grade:

Country

Construction:

7-ply hardwood

Wear Layer:

3 mm sawn cut, live sawn

Glue

Carb II, TSCA Title 6 EPA certified

Style:

Wire brushed, bevel 4-sides

Tongue & groove

Finish:

UV-cured Urethane, brush matte, 7 - 10% gloss Static Friction Coefficient (ASTM D 2047): slip resistance < 0.5

Warranty:

25 Years Surface (3-Year Light Commercial), Lifetime Structural

Coverage:

20.92 sq ft / carton

Installation:

Glue, float or nail with glue assist

Subfloor:

Wood, concrete or radiant floor systems

Radiant Heat:

Yes, glue down or floating installation > 83° F

ENVIRONMENT: No harmful VOC, Lacey Act compliant, LEED credits -

CERTIFIED MANUFACTURING:

- Lacey Act compliant
- No halogenated hydrocarbons, herbicides, heavy metals
- Carb II, TSCA Title 6 EPA certified

GREEN BUILD STATEMENT:

Du Monde Hardwood Flooring may contribute to attaining points within the Environmental Quality section of the LEED rating system. The determining factor for indoor quality is the quantity of noxious emanations from volatile compounds in adhesives and finishes.

TEST RESULTS:

Delamination Test:

ANSI/HPVA Bond Line 3 Cycle Test: 100% Pass

Critical Radial Flux:

avg 0.37 w/cm2 ASTM E 648, Class 2 NFPA Life Safety Code 101

NWFA Janka (Hardness):

1200 lbs

Surface Burning:

ASTM E84 Class C

Smoke Density:

Avg.DMC 281-389 Non Flaming ASTM E 662