

Product Specification

Barnes Mill

Style Name:	Solid Seringa
Description:	Handscraped with T&G
Application:	Suitable for Floor and Wall
Species:	Seringa
Construction:	Dry-sawn
Sizes:	Width: 115mm x 2200mm – approx: 4-1/2" x 86.68" (RL) Thickness: 18mm total thickness - approx: 3/4"
Packing:	21.82 sq. ft/carton, 56 cartons/pallet, container: 16 pallets/40 ft. = 19,550.7 sq. ft
Edge:	Slight 1mm micro bevel
Finish:	Stained, UV cured Polyurethane, carbide enhanced anti scratch top coat, Silk matt, 10-12 % gloss. Solvent free, 100% solid, Non-off gassing, ECO-certificed Resandable
Grade:	Country Grade: Knots not to exceed 1" in diameter
Stain:	Custom upon request
Trim Pieces:	Quarter Round, T-Molding, Reducer, Baby Threshold, Stair Nose
Installation:	Nail down installation
Warranty:	25-Year Residential, 3-Year Light Commercial - Lifetime structural warranty
Tests:	Critical Radiant Flux: avg. 0.38 w/cm ² ASTM E 648-06. >Class 2 NFPA Life Safety Code 101 Surface Burning: ASTM E84 Class B Smoke Density: Average Dmc 329 Flaming – 467 Non Flaming ASTM E 662 Static Coefficient of Friction: Dry: 0.555 Wet: 0.882 ASTM D2394-05 Moisture Content: >6% to <9% ASTM D 4442
Certified Manufacturing:	100% PEFC Pure materials Lacey Act Compliance CARB II Compliant, no halogenated hydrocarbons, herbicides, heavy metals PROP 65 Compliant
Green Build Statement:	May contribute to attaining points within the Environmental Quality section of the LEED® Rating Systems. The determining factor for indoor air quality is the quantity of noxious emanations from volatile organic compounds in adhesives and finishes.

