

Product Specification

Style Name:	DuMonde
Description:	French White Oak Wire Brushed with T&G
Application:	Suitable for Floor and Wall
Species:	Top layer: White Oak Core: Hardwood plywood Back: Hardwood ply
Construction:	Dry-sawn, Hardwood Plywood Core
Sizes:	Plank: Width: 180mm x 1800mm – approx: 7" x 71" (RL) Thickness: 12.7mm total thickness - approx: 1/2"
Packing:	20.92 sq. ft/carton, 55 cartons/pallet, container: 20 pallets/40 ft. = 23,012.0 sq. ft
Edge:	Slight 1mm micro bevel
Finish:	Wire Brushed and stained, UV cured Polyurethane, carbide enhanced anti scratch top coat, 10 +/- 2% gloss. Solvent free, 100% solid, Non-off gassing, Prop 65 Certified
Grade:	Country Grade: Knots not to exceed 1-1/2" in diameter
Stain:	Custom upon request
Trim Pieces:	Quarter Round, T-Molding, Reducer, Baby Threshold, Stair Nose
Installation:	Staple, glue or floating installation. Radiant heat compatible
Warranty:	25-Year Residential, 3-Year Light Commercial - Lifetime structural warranty
Tests:	Critical Radiant Flux: avg. 0.38 w/cm ² ASTM E 648-06. >Class 2 NFPA Life Safety Code 101 Surface Burning: ASTM E84 Class B Smoke Density: Average Dmc 329 Flaming – 467 Non Flaming ASTM E 662 Static Coefficient of Friction: Dry: 0.555 Wet: 0.882 ASTM D2394-05 Moisture Content: >6% to <9% ASTM D 4442 Delamination test: ANSI/HPVA Bond Line 3 cycle Test 100% pass
Certified Manufacturing:	100% PEFC Pure materials Lacey Act Compliance CARB II Compliant, no halogenated hydrocarbons, herbicides, heavy metals Prop 65 Compliant
Green Build Statement:	May contribute to attaining points within the Environmental Quality section of the LEED® Rating Systems. The determining factor for indoor air quality is the quantity of noxious emanations from volatile organic compounds in adhesives and finishes.

