




ARTISANO
PARQUET

COLOR:
SANIBEL

SKU #:
12758PP



Height: 1/2" Length: 23-5/8"

All dimensions are nominal



Your floor may vary due to color treatment, natural tannin variations and knots.

Wood Species:

French White Oak

Grade:

Country

Construction:

7-ply hardwood

Wear Layer:

3 mm sawn cut, live sawn

Glue:

Carb II, TSCA Title 6 EPA certified

Style:

Wire brushed, bevel 4-sides, T&G +ST
Fumed and lime-washed colors

Finish:

UV-cured Urethane, brush matte, 7 - 10% gloss

Static Friction Coefficient (ASTM D 2047): slip resistance < 0.5

Warranty:

25 Years Surface (3-Year Light Commercial), Lifetime Structural

Coverage:

18.60 sq ft / carton

Installation:

Glue, float or nail with glue assist

Subfloor:

Wood, concrete or radiant floor systems

Radiant Heat:

Yes, glue down or floating installation > 83° F

ENVIRONMENT: **No harmful VOC, Prop 65 certified, LEED credits**

CERTIFIED MANUFACTURING:

- 100% PEFC (PanEuro Forest Council) material
100% chain of custody from forest to jobsite
- Lacey Act compliant
- No halogenated hydrocarbons, herbicides, heavy metals
- No added Urea Formaldehyde, NAF

GREEN BUILD STATEMENT:

Artisano Hardwood Flooring may contribute to attaining points within the Environmental Quality section of the LEED rating system. The determining factor for indoor quality is the quantity of noxious emanations from volatile compounds in adhesives and finishes.

TEST RESULTS:

Emissions Test:

CA - DPH specification 01350 (Prop 65): Pass

Delamination Test:

ANSI/HPVA Bond Line 3 Cycle Test: 100% Pass

Critical Radial Flux:

avg 0.37 w/cm2 ASTM E 648, Class 2 NFPA Life Safety Code 101

NWFA Janka (Hardness):

1200 lbs

Surface Burning:

ASTM E84 Class C

Smoke Density:

Avg.DMC 281-389 Non Flaming ASTM E 662